TECHNICAL FILE

4600 PLUS LIFT & SLIDE TB

Transmittance

$U_w \geq 0.65$ (W/m²K)

Consult typology, dimensions and glass.

Acoustic insulation

Maximum glazing	**65 mm**
Minimum glazing	**22 mm**

Sightlines

Frame	180 mm, 280 mm 3 rails, 380 mm 4 rails
Sash	80 mm

Maximum dimensions / Sash

Width (L) = 3,300 mm

Height (H) = 3,500 mm

Consult maximum weight and dimensions according to typologies.

Maximum weight / Sash

400 kg

Categories achieved at test centre

Protection against atmospheric agents.

Air permeability
(UNE-EN 12207): Class 4

Water tightness
(UNE-EN 12208): Class E750*

Wind resistance
(UNE-EN 12210): Class C5**

* Reference test 4.0 x 2.5 m / 1 sash + 1 fixed light
**Reference test 4.0 x 2.5 m / 2 sashes

Test verified by
ALUMINIOS CORTIZO S.A.U.

Extrusion alloy

6063 T-5

Finishes

Possibility of dual colour.

Colour powder coating (RAL, mottled & rough).
According to Qualicoat >60 microns

Wood effect powder coating.
According to Qualideco standard

Anodised.
According to Ewwa Euras / Standard Class 15 / Optionally Class 20 and 25

Opening possibilities

Sliding

1 rail (1 sash + 1 fixed light), 2, 3 & 4 rails

Possibility of 90° opening without mullion

